

# How to Measure COVERALLS 1.800.803.9256

#### CHEST

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance across directly under arm from side seam to side seam
- Double distance measured to determine circumference

# **NECK**

- With garment open, lay flat with front side up making certain to eliminate all slack
- · Measure from center of facing along collar seam to center of opposite facing
- · Distance measured is neck opening

# **SHOULDER LENGTH**

- Measure distance along shoulder seam from base of neck to armhole seam
- Shoulder length measurement does not apply to full ragian sleeve garments

#### **ACROSS BACK**

- With garment closed, lay flat with back side up making certain to eliminate all slack
- Measure distance between armhole seams approximately 9" down from base of neck
- Distance measured is across back measurement

#### SLEEVE LENGTH

- With garment closed, lay flat with back side up making certain to eliminate all slack
- Measure from center back at base of neck across shoulder to bottom of wrist opening
- Distance measured is sleeve length
- NOTE: True sleeve length is measured with garment on and arm raised chest high with elbow bent at 90 degree angle to the front.

### **CUFF At WRIST**

- Lay sleeve flat and measure distance across opening at wrist
- Double distance measured to determine circumference
- NOTE: For garments with vented sleeve, measure when closed to first adjustment

# **WAIST**

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance across finished waist from side seam to side seam
- Double distance measured to determine circumference

# **HIPS / SEAT**

- With garment closed, lay flat with back side up making certain to eliminate all slack
- Measure distance across widest point between top of waist and crotch seam approximately 9" down from top of waist
- Double distance measured to determine circumference

### THIGH

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance from crotch point across to outside of leg
- Double distance measured to determine circumference

#### **KNEE**

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Fold bottom of pant leg up to crotch seam
- Measure distance across at half way point determined by fold line
- Double distance measured to determine circumference

## **LEG CUFF**

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance across finished opening at bottom of pants leg
- Double distance measured to determine circumference

## **INSEAM LENGTH**

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance from crotch seam to bottom of pants leg along inside seam
- Distance measured is inseam length

## **GARMENT OVERALL LENGTH**

- With garment closed, lay flat with back side up making certain to eliminate all slack
- Measure distance from center back neck at collar seam to leg bottom of finished garment
- Distance measured is garment overall length

## TORSO / TRUNK LENGTH

Deduct the inseam length from the garment overall length to determine torso / trunk length

# **FRONT RISE**

- With garment closed, lay flat with front side up making certain to eliminate all slack
- Measure distance from crotch seam up to seam at waist joining top to bottom
- Distance measured is front rise

#### **BACK RISE**

- With garment closed, lay flat with back side up making certain to eliminate all slack
- Measure distance from crotch seam up to seam at waist joining top to bottom along seat seam
- Distance measured is back rise