

## Technical Data

### Plug-in Units

Plug-in Unit	Maximum Amperes	Maximum ac Volts	Dimensions in Inches (mm)						Mechanical Terminal Wire Range Per Phase (mm <sup>2</sup> )	Approx. Weights Lbs. (kgs)
			(A) <sup>G)</sup>	(B)	(C)	(D)	(E)	(F)		

#### Circuit Breaker Plug-in Units

P3BFD (E- & F-Frame Breakers)	225	600	19.26 (489.2)	12.36 (314.0)	5.43 (138.0)	6.25 (158.8)	4.00 (101.6)	6.06 (153.7)	100 A - (1) #14 - 1/0 (2.5 - 50) 150 A - (1) #4 - 4/0 (25 - 95)	25 (11.3)
P3BJD (J-Frame Breakers)	250	600	21.33 (541.8)	12.36 (314.0)	6.97 (177.0)	10.44 (265.2)	4.00 (101.6)	6.06 (153.7)	250 A - (1) #14 - 350 kcmil (25 - 185) 225 A - (1) 3 - 350 kcmil (35 - 185)	47 (21.3)
P3BKD (K-Frame Breakers)	400	600	32.50 (825.5)	13.29 (337.6)	7.79 (197.9)	12.56 (319.0)	4.00 (101.6)	6.64 (168.7)	350 A - (1) 250 - 500 kcmil (120 - 240) 400 A - (2) 3/0 - 250 kcmil (45 - 120)	53 (24.0)
P3BLD (L-Frame Breakers)	600	600	44.03 (1118.4)	19.65 (499.1)	10.15 (257.8)	17.38 (441.5)	4.00 (101.6)	9.83 (249.7)	400 A - (1) 4/0 - 600 kcmil (120 - 300) 600 A - (2) 400 - 500 kcmil (185 - 240)	75 (34.0)
P3BMD (M-Frame Breakers)	800	600	44.03 (1118.4)	19.65 (499.1)	10.15 (257.8)	17.38 (441.5)	4.00 (101.6)	9.83 (249.7)	600 A - (2) #1 - 500 kcmil (50 - 240) 800 A - (2) 500 - 750 kcmil (300 - 400)	136 (61.7)
P3BND (N-Frame Breakers)	800	600	44.03 (1118.4)	19.65 (499.1)	10.15 (257.8)	17.38 (441.5)	4.00 (101.6)	9.83 (249.7)	700 A - (2) #1 - 500 kcmil (50 - 240) 800 A - (3) 3/0 - 400 kcmil (95 - 185)	138 (62.6)
P3BLAP (TRI-PAC)	400	600	44.03 (1118.4)	19.65 (499.1)	10.15 (257.8)	13.80 (350.5)	4.00 (101.6)	9.83 (249.7)	225 A - (1) #6 - 350 kcmil (16 - 185) 400 A - (1) #4 - 250 kcmil and (1) 3/0 - 600 kcmil (25 - 120 and 95 - 300)	96 (43.5)
P3BLCL	400	600	40.00 (1016.0)	19.65 (499.1)	10.15 (257.8)	13.80 (350.5)	4.00 (101.6)	9.83 (249.7)	(1) #4 - 250 kcmil (25 - 120) and (1) 3/0 - 600 kcmil (95 - 300)	88 (39.9)

#### Fusible Plug-in Units

P3F321R P3F361R and P3F361H	30	240 600	20.85 (529.6)	12.36 (314.0)	5.43 (138.0)	7.88 (200.2)	4.00 (101.6)	6.06 (153.9)	Cu - (1) #14 - #3, (2.5 - 35) Al - (1) #12 - #2 (3.2 - 35)	22 (10.0)
P3F322R  P3F362R and P3F362H	60	240 600	20.85 (529.6)	12.36 (314.0)	5.43 (138.0)	7.88 (200.2)	4.00 (101.6)	6.06 (153.9)	Cu - (1) #14 - #3, (2.5 - 35) Al - (1) #12 - #2 (3.2 - 38)  Cu - (1) #14 - 1/0, (2.5 - 50) Al - (1) #12 - 1/0 (3.2 - 50)	24 (10.9)
P3F323R and  P3F363R and P3F363H	100	240 600	20.85 (529.6)	12.36 (314.0)	5.43 (138.0)	7.88 (200.2)	4.00 (101.6)	6.06 (153.9)	Cu - (1) #14 - 1/0, (2.5 - 50) Al - (1) #12 - 1/0 (3.2 - 50)  (1) #4 - 250 kcmil Cu/Al (25 - 120)	24 (10.9)
P3F324R and P3F364R	200	240 600	23.52 (597.4)	15.56 (395.2)	7.19 (182.6)	7.98 (202.7)	4.00 (101.6)	7.63 (193.8)	(1) #4 - 250 kcmil Cu/Al (25 - 120) (1) #4 - 600 kcmil Cu/Al (25 - 300) or (2) 250 kcmil (120)	47 (21.3)
P3F364H	200	600	21.75 (552.5)	15.56 (395.2)	9.66 (245.4)	6.28 (159.5)	4.00 (101.6)	7.63 (193.8)		
P3F325R and P3F365R	400	240 600	46.94 (1192.3)	21.22 (539.0)	10.07 (255.8)	12.67 (321.8)	4.00 (101.6)	10.69 (271.5)	(1) 250 - 750 kcmil Cu/Al (127 - 380) (2) 3/0 - 250 kcmil Cu/Al (85 - 127)	77 (34.9)
P3F365H	400	600	21.67 (550.4)	21.22 (539.0)	21.00 (533.4)	12.67 (321.8)	4.00 (101.6)	10.69 (271.5)	(1) 250 - 750 kcmil Cu/Al (127 - 380) (2) 3/0 - 250 kcmil Cu/Al (85 - 127)	81 (36.7)
P3F326R and P3F366R	600	240 600	46.94 (1192.3)	26.31 (668.3)	10.59 (270.0)	14.26 (362.2)	4.00 (101.6)	13.16 (334.3)	(2) #2 - 600 kcmil Cu/Al (35 - 300) (3) #4 - 600 kcmil Cu/Al (25 - 300)	82 (37.1)
P3F327R and P3F367R	800	240 600	46.94 (1192.3)	26.31 (668.3)	10.59 (270.0)	14.26 (362.2)	4.00 (101.6)	13.16 (334.3)	(3) #4 - 600 kcmil Cu/Al (25 - 300)	108 (49.0)

<sup>G)</sup> The Clamp and Guide mechanism adds 2.50 inches (63.5 mm) to the overall length of the unit.

CSA is a registered trademark of the Canadian Standards Association. NEMA is the registered trademark and service mark of the National Electrical Manufacturers Association. UL is a federally registered trademark of Underwriters Laboratories Inc. Uniform Building Code (UBC) is a trademark of the International Conference of Building Officials (ICBO).

Eaton Electrical Inc.  
1000 Cherrington Parkway  
Moon Township, PA 15108  
United States  
tel: 1-800-525-2000  
www.EatonElectrical.com

©2004 Eaton Corporation All  
Rights Reserved Printed in USA  
Pub. No. PA01701001E / Z2833  
December 2004